


+

FIG 1: current frequency

1/14



$$p = \text{pulse duration} = T / 3$$

$$T = \text{time of one cycle} = 1 / f$$

$$f = \text{drive frequency in Hz}$$

$$f = c / (3 a) \text{ where } a = \text{segment length} = \text{plate separation in metres}$$

Distance 'a' is fixed for a particular SCAM, but is flexible to support SCAMs of different scales. Typical values for 'a' would range from 1 cm to 1 km

For example, if $a = 1 \text{ cm}$, ie 10^{-2} m , then

$$f = 3 \times 10^8 / (3 \times 10^{-2}) = 10^{10} \text{ Hz, ie } 10 \text{ GHz}$$


$$T = 1 / 10^{10} = 10^{-10} \text{ seconds, and } p = 10^{-10}/3 \text{ seconds}$$

+

+

FIG 2: phasing chart

2/14



$p = \text{pulse duration} = T / 3$

$T = \text{time of one cycle}$

$f = \text{drive frequency in Hz}$

$f = c / (3 a)$ where $a = \text{segment length} = \text{plate separation in metres}$

Distance 'a' is fixed for a particular SCAM, but is flexible to support SCAMs of different scales. Typical values for 'a' would range from 1 cm to 1 km

For example, if $a = 1 \text{ cm}$, ie 10^{-2} m , then


$f = 3 \times 10^8 / (3 \times 10^{-2}) = 10^{10} \text{ Hz}$, ie 10 GHz

$T = 1 / 10^{10} = 10^{-10} \text{ seconds}$, and $p = 10^{-10}/3 \text{ seconds}$

+

+

FIG 3: x and z separation of 2 segments, ie segment pair




Distance 'a' is fixed for a particular SCAM, but is flexible to support SCAMs of different scales. Typical values for 'a' would range from 1 cm to 1 km

+

+

FIG 4: x and z separations of neighboring segments




Distance 'a' is fixed for a particular SCAM, but is flexible to support SCAMs of different scales. Typical values for 'a' would range from 1 cm to 1 km

+

+

FIG 5: x and y separations in a single plate

5/14




Distance 'a' is fixed for a particular SCAM, but is flexible to support SCAMs of different scales.
 Typical values for 'a' would range from 1 cm to 1 km

+

+

FIG 6: z and y separation in two plates




Distance 'a' is fixed for a particular SCAM, but is flexible to support SCAMs of different scales. Typical values for 'a' would range from 1 cm to 1 km

+

+

FIG 7: perspective view of the two plates


7/14



Distance 'a' is fixed for a particular SCAM, but is flexible to support SCAMs of different scales.
Typical values for 'a' would range from 1 cm to 1 km

+


FIG 8: close-up perspective view of the two plates and current segments
Distance 'a' is fixed for a particular SCAM, but is flexible to support SCAMs of different scales. Typical values for 'a' would range from 1 cm to 1 km



+

FIG 9: m-n segment distance relationship

9/14




Distance 'a' is fixed for a particular SCAM, but is flexible to support SCAMs of different scales. Typical values for 'a' would range from 1 cm to 1 km

+

+

FIG 10: Force between current-carrying conducting wires

10/14



I current in the wires


In this theoretical description, the values of a , h_1 , h_2 , l_1 , l_2 and I are variable

+

+

FIG 11: Plate 1 (0,0) to Plate 2 (m,n) segment distance, B

11/14




Distance 'a' is fixed for a particular SCAM, but is flexible to support SCAMs of different scales. Typical values for 'a' would range from 1 cm to 1 km

+

+

FIG 12: timing differences

12/14



Explanation of time units

$p = \text{pulse duration} = T / 3$, $T = \text{time of one cycle} = 1 / f$, $f = \text{drive frequency in Hz}$
 $f = c / (3 a)$ where $a = \text{segment length} = \text{plate separation in metres}$

Distance 'a' is fixed for a particular SCAM, but is flexible to support SCAMs of different scales.
Typical values for 'a' would range from 1 cm to 1 km

For example, if $a = 1 \text{ cm}$, ie 10^{-2} m , then
 $f = 3 \times 10^8 / (3 \times 10^{-2}) = 10^{10} \text{ Hz}$, ie 10 GHz
 $T = 1 / 10^{10} = 10^{-10} \text{ seconds}$, and $p = 10^{-10}/3 \text{ seconds}$


Note: due to the Plate 2 phase shift of p , the Plate 1 arrival times are delayed (right-shifted) by p

+

+

FIG 13: Gazette view

13/14



Distance ' a ' is fixed for a particular SCAM, but is flexible to support SCAMs of different scales.
 Typical values for ' a ' would range from 1 cm to 1 km

+

+

FIG 14: Relativistic force between current-carrying conducting wires





FIG 15 Lorentz length contraction



+